

Cooling Only

Model			UATQ60C	UATQ90C	UATQ120C	UATQ150C	UATQ180C	UATQ210C	UATQ240C	UATQ300C
Cooling T1 ⁽¹⁾ 35°C (Nominal)	Capacity	Btu/h	61,000	90,000	121,500	150,000	181,000	213,000	241,000	304,000
	Capacity	kW	17.88	26.38	35.61	43.96	53.05	62.43	70.63	89.10
	EER	(Btu/h) / W	13.01	11.80	12.20	12.00	11.70	12.00	11.90	11.90
	EER	W/W	3.81	3.46	3.58	3.52	3.43	3.52	3.49	3.49
	PI	kW	4.69	7.63	9.96	12.50	15.47	17.75	20.26	25.54
Cooling T3 ⁽²⁾ 46°C	Capacity	Btu/h	51,780	77,000	103,300	129,000	156,000	184,000	208,000	258,000
	Capacity	kW	15.18	22.57	30.27	37.81	45.72	53.93	60.96	75.61
	EER	Btu/h	8.80	8.55	8.60	8.55	8.55	8.95	8.70	8.45
	PI	kW	5.89	9.01	12.01	15.08	18.25	20.55	23.90	30.53
Indoor External Static Pressure		Pa	50-500	50-500	50-500	50-500	50-500	50-500	50-500	50-500
Airflow		cfm	2000	2800	4400	5000	7000	7600	8000	9000
Outdoor Sound Performance	Sound Pressure	dBA	61	62	65	67	68	69	70	72
	Sound Power	dBA	81	83	83	85	87	89	89	92
Dimensions	Height	mm	1,150	1,350	1,390	1,390	1,690	1,650	1,650	1,950
	Width	mm	1,280	1,280	1,965	1,965	1,965	2,410	2,410	2,410
	Depth	mm	1,520	1,520	1,630	1,630	1,905	2,030	2,030	2,030
Weight	Net	kg	350	380	590	650	840	930	940	1,090
	Gross	kg	370	400	620	680	870	970	980	1,130
Cooling		°CDB	19-52							
Refrigerant			R-410A							
Power Supply		V/Ph/Hz	380-415/3/50							

(1) Rated cooling capacity based on 27°CDB / 19°CWB indoor and 35°C CDB outdoor

(2) Rated cooling capacity based on 29°CDB / 19°CWB indoor and 46°C CDB outdoor



Powerful Cooling

Rapid cooling and powerful, even if outside temperature is very high.



R-410A

Zero ozone depletion potential for a reduced impact on the environment.



Energy Saving

Daikin offers efficient operation on its equipment for lower electricity consumption. This also contributes to reduce CO₂ emissions.



User Friendly

Easy installation, easy operating procedures and friendly shape buttons.



Tropical Compressor

The tropical compressor is able to handle and operate fully under extreme weather conditions.

DAIKIN MIDDLE EAST AND AFRICA FZE

P.O. Box 18674, Jebel Ali Free Zone, Dubai, UAE, Tel: +971 (0) 4 815 9300, Fax: +971 (0) 4 815 9311

Email: info@daikinmea.com Web: www.daikinmea.com



Daikin Middle East and Africa



DMEA20-084A GCC